


# Bridge Jacks

These optional bridge jacks can be added to any of our four-post models for the ultimate in jacking speed and convenience. Perfect for wheel and suspension work. Each jack comes complete with stackable adapters and a 10,000 PSI air/hydraulic pump that provides a smooth controlled operation.

Model(s) RJ-45 / RJ-7




Model RJ-9



MODEL	RJ-9
Lifting Capacity	4,500 lbs. / 2041 Kg.
A - Min. Width	35" / 889 mm.
A - Max. Width	45-1/2" / 1156 mm.
B - Min. Pad & Adapter	8" / 203 mm.
B - Min. Pad Only	4-1/2" / 114 mm.
B - Max. Pad & Adapter	18" / 457 mm.
B - Max. Pad Only	14-1/2" / 368 mm.
Min. Arm Reach	40-1/4" / 1022 mm.
Max. Arm Reach	63-1/4" / 1607 mm.

The design, material and specifications are subject to change without notice.


Model(s) RJ-12 / RJ-15



MODEL	RJ-7
Lifting Capacity	7,000 lbs. / 3175 Kg.
A - Min. Width	35" / 889 mm.
A - Max. Width	45-1/2" / 1156 mm.
B - Min. Pad & Adapter	10" / 254 mm.
B - Min. Pad Only	6-1/2" / 162 mm.
B - Max. Pad & Adapter	20" / 508 mm.
B - Max. Pad Only	16-1/2" / 419 mm.
Min. Arm Reach	40-1/4" / 1022 mm.
Max. Arm Reach	63-1/4" / 1607 mm.


The design, material and specifications are subject to change without notice.

Model(s) RJ-18 / RJ-25



MODEL	RJ-9
Lifting Capacity	9,000 lbs. / 4082 Kg.
A - Min. Width	41" / 1041 mm.
A - Max. Width	51-1/2" / 1308 mm.
B - Min. Pad & Adapter	13-1/4" / 337 mm.
B - Min. Pad Only	9-3/4" / 248 mm.
B - Max. Pad & Adapter	23-1/4" / 591 mm.
B - Max. Pad Only	19-3/4" / 502 mm.
Min. Arm Reach	40-1/4" / 1022 mm.
Max. Arm Reach	63-1/4" / 1607 mm.

The design, material and specifications are subject to change without notice.



MODEL	RJ-12	RJ-15	RJ-18	RJ-25
Lifting Capacity	12,000 lbs. / 5443 Kg.	15,000 lbs. / 6804 Kg.	18,000 lbs. / 8,165 Kg.	25,000 lbs. / 11,340 Kg.
A - Min. Width	44" / 1118 mm.	44" / 1118 mm.	48" / 1188 mm.	48" / 1188 mm.
A - Max. Width	58" / 1473 mm.	58" / 1473 mm.	60" / 1524 mm.	60" / 1524 mm.
B - Min. Short Pad	14" / 356 mm.	14" / 356 mm.	15-1/2" / 394 mm.	15-1/2" / 394 mm.
B - Max. Short Pad	23" / 584 mm.	23" / 584 mm.	24-1/2" / 622 mm.	24-1/2" / 622 mm.
B - Min. Tall Pad	17" / 432 mm.	17" / 432 mm.	18-1/2" / 470 mm.	18-1/2" / 470 mm.
B - Max. Tall Pad	20" / 508 mm.	20" / 508 mm.	27-1/2" / 699 mm.	27-1/2" / 699 mm.
C - Min. Short Pad	19" / 483 mm.	19" / 483 mm.	19" / 483 mm.	19" / 483 mm.
C - Max. Short Pad	26" / 711 mm.	26" / 711 mm.	28" / 711 mm.	28" / 711 mm.
C - Min. Tall Pad	22" / 559 mm.	22" / 559 mm.	22" / 559 mm.	22" / 559 mm.
C - Max. Tall Pad	31" / 787 mm.	31" / 787 mm.	31" / 787 mm.	31" / 787 mm.
D - Min. Arm Reach	45" / 1143 mm.	45" / 1143 mm.	48" / 1219 mm.	48" / 1219 mm.
D - Max. Arm Reach	58" / 1473 mm.	58" / 1473 mm.	64" / 1626 mm.	64" / 1626 mm.
E - Wheel Assembly Width	19-1/2" / 495 mm.	19-1/2" / 495 mm.	23-1/4" / 591 mm.	23-1/4" / 591 mm.
F - Overall Width	22-1/2" / 571 mm.	22-1/2" / 571 mm.	26" / 660 mm.	26" / 660 mm.

The design, material and specifications are subject to change without notice.